Microdot: A Four-Bit Microcontroller Designed for Distributed Low-End Computing in Satellites

By Air Force Institute of Technology (U. S.). Graduate School of Engineering and Management

Biblioscholar Sep 2012, 2012. Taschenbuch. Book Condition: Neu. 246x189x9 mm. This item is printed on demand - Print on Demand Neuware - As satellites become more complex, the on-board processing capabilities must keep up. Many satellites are an integrated collection of sensors and actuators with many requiring dedicated real-time control to operate correctly. For single processor systems, adding more sensors requires an increase in computing power and speed to provide the multi-tasking capability needed to service each sensor. Faster processors are more costly and consume more power, which can tax a satellite's power resources and may lead to shorter satellite lifetimes. Commercial-Off-The-Shelf (COTS) electronic components are usually not acceptable for satellite design because they have not been hardened against the radiation environment of space. An alternative design approach is to use a distributed network of small and low power microcontrollers designed for space to handle the computing requirements of each individual sensor and actuator. The design of microdot, a four-bit microcontroller for distributed low-end computing, is presented. The design is based on previous research completed at the Space Electronics Branch, Air Force Research Laboratory (AFRL/VSSE) at Kirtland AFB, NM, and the Air Force Institute of Technology at Wright- Patterson AFB,...

READ ONLINE